

{W:\20794\0205078us0\00820309.DOC }

means of the positioning motor such a manner that the door can be automatically moved from its closed position to a predetermined open position and vice versa. This is done using a sensor in the form of a temperature sensor. In the known cooking appliance, the door is automatically moved from the closed position to the open position after a cooking process in the form of a baking process is complete. The heat and vapor can gradually escape from the cooking chamber through the gap between the door and the housing.

[0004] Furthermore, DE 295 14 690 U1 discloses the use of a shape-memory element in an automatic venting device to automatically open a window.

[0005] Furthermore, it is known from DE 43 38 584 A1 to use a return element in the form of a spring in a device for thermally treating materials in order to sealingly close a heating chamber that can be closed by a door. There, the spring is mounted on a hinge rod of a hinge-type mounting arrangement of the door.

SUMMARY OF THE INVENTION

[0006] It is, ~~therefore~~, an object of the present invention to further improve the ease of use for the user.

[0007] ~~This object is achieved in accordance with the present invention by a method having the features of Claim 1.~~ The present invention provides a method for operating a cooking appliance including a cooking chamber, which is bounded by a housing and a door in its closed position, and further including a cooking appliance control system, the door being automatically openable by the cooking appliance control system by means of a door opening device, the door being automatically moved from the closed position to the open position when the cooking process is complete, wherein, after the aforementioned movement to the open position, the door is automatically returned to the closed position when a physical quantity falls below a predetermined threshold value stored in a memory of the cooking appliance control system.

[0008] In addition to the improved user convenience provided by automatically moving the door from the closed position to the open position when the cooking process is complete, and by automatically returning the door to the closed position after a physical quantity falls below

[0010] This object is achieved in accordance with the present invention by a cooking appliance having the features of Claim 2. The present invention also provides a cooking appliance, in particular a steam cooking appliance, comprising a cooking chamber which is bounded by a housing and a door in its closed position, and further comprising a cooking appliance control system, the door being automatically openable by the cooking appliance control system by means of a door opening device, the door opening device including a positioning motor and a rod, and the rod being capable of being automatically reciprocated by the cooking appliance control system by means of the positioning motor such a manner that the door can be automatically moved from its closed position to a predetermined open position and vice versa, the cooking appliance control system actuating the positioning motor as a function of the output signal of a sensor located in the cooking chamber, and the cooking appliance control system actuating the positioning motor in such a manner that the door is automatically moved from the closed position to the open position when the cooking process is complete, wherein the rod can be reciprocated in a guide means, and the cooking appliance control system actuates the positioning motor in such a manner that the door is automatically returned to the closed position when a physical quantity falls below a predetermined threshold value stored in the memory. Advantageous embodiments and refinements of the present invention will become apparent from the following dependent claims.

{W:\20794\0205078us0\00820309.DOC 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 }3

[0017] An exemplary embodiment of the present invention is shown in the only drawing figure in a purely schematic way and will be described in more detail below.

[0018] The Figure is a cross-sectional side view of a cooking appliance according to the present invention.

DETAILED DESCRIPTION

[0019] In the Figure, there is shown a cooking appliance in the form of a steam cooking appliance for carrying out the method of the present invention. The cooking appliance has a cooking chamber 2, which is bounded by a housing 4 and a door 6 in its closed position. In the Figure, door 6 is shown in its open position. Door 6 is held to housing 4 in a conventional manner by a hinge (not shown in the Figure), which is mounted on housing 4 and located in the lower portion of housing 4 when the cooking appliance is in the operating position. The hinge allows door 6 to pivot to a position approximately horizontal with respect to the operating position. The hinge has a return element (not shown in the Figure), which takes the form of a return spring and is in force-transmitting connection with housing 4 and door 6. The return element aids in moving door 6 toward the closed position. In the present exemplary embodiment, the cooking appliance of the present invention has a fan (not shown in the Figure), which sucks out vapors from cooking chamber 2 and discharges the vapors into the open environment mainly through a flow channel and an outlet 7 which is provided on the front of the cooking appliance and located above door 6 when the cooking appliance is in the operating position.

[0020] The cooking appliance further has a cooking appliance control system (not specifically shown in the Figure), door 6 being automatically openable by the cooking appliance control system by means of a door opening device 8. The cooking appliance control system includes a temperature sensor (also not shown in the Figure), which is located in cooking chamber 2. The cooking chamber temperature measured by the temperature sensor is converted to an output signal and transmitted to a processing unit of the cooking appliance control system. A threshold value for the cooking chamber temperature is stored as a physical quantity in a memory of the cooking appliance control system.

[0021] Door opening device 8 includes a positioning motor 8.1 in the form of an electrically heatable shape-memory element, a rod 8.2, and a guiding means 8.3 for rod 8.2. Rod 8.2 can

be automatically reciprocated in guide means 8.3 by the cooking appliance control system by means of positioning motor 8.1 in such a manner that door 6 can be automatically moved from its closed position to the predetermined open position, and vice versa. In the present exemplary embodiment, the open position shown in the Figure is defined such that door 6 is open approximately 1 degree in the open position. Rod 8.2 is designed in two parts, a spring means 8.4 in the form of a spiral spring being arranged between the two parts of rod 8.2. Spring means 8.4 is inserted in a sleeve-like receptacle on one part of rod 8.2. The other part of rod 8.2 engages, with one end, in the sleeve-like receptacle and is movably guided in the sleeve-like receptacle. At the same time, spring means 8.4 is thereby held in place. Apart from that, the above-mentioned components of door opening device 8 are force-transmittingly connected to each other in a manner known to those skilled in the art.

[0022] In the following, the operation of the cooking appliance of the present invention, and thus of the method according to the present invention, will be explained in greater detail with reference to the Figure.

[0023] The cooking appliance is on, food to be cooked is placed in cooking chamber 2, and door 6 is in the closed position, so that cooking chamber 2 is closed in a substantially sealing manner. The completion of the cooking process is detected by the cooking appliance control system in a manner known to those skilled in the art, for example, based on the signal of a timing element in the cooking appliance control system, or by means of a sensor located in cooking chamber 2. Once the cooking appliance control system has detected the completion of the cooking process, the electrical heater of positioning motor 8.1, which is in the form of a shape-memory element, is connected to an electrical voltage, so that the shape-memory material, which is wax in this exemplary embodiment, expands, moving a plunger of positioning motor 8.1 out of the housing of positioning motor 8.1 and toward door 6, substantially along the longitudinal axis of rod 8.2. Since one part of rod 8.2 is force-transmittingly connected to the plunger of positioning motor 8.1, this part of rod 8.2 also moves toward door 6 substantially along the longitudinal axis of rod 8.2, which is guided in guide means 8.3. In the process, spring means 8.4 is initially slightly compressed along the longitudinal axis of rod 8.2 before the force introduced by the expanding wax is transmitted by said spring means to the other part of rod 8.2. Once the other part of rod 8.2 is in force-transmitting connection with door 6 and the spring force of the return element is overcome,

door 6 is moved by door opening device 8 from the closed position to the open position and retained therein against the spring force of the return element.

[0024] When door 6 is in the open position, excess heat and/or vapor can escape from cooking chamber 2 into the open environment, so that cooking chamber 2 cools down. In accordance with the present exemplary embodiment, in order to accelerate this process, the cooking appliance control system leaves the fan on, or turns the fan on, after the cooking process is complete, so that a flow of air or vapors emerging from outlet 7 above door 6 promotes the exchange of air in cooking chamber 2.

[0025] The cooking chamber temperature is measured by the temperature sensor located in cooking chamber 2 during the entire processes explained above, and thereafter, converted into an output signal, and transmitted to the processing unit of the cooking appliance control system. When, after door 6 has been opened, the cooking chamber temperature measured by the temperature sensor falls below the predetermined threshold value stored in the memory of the cooking appliance control system, the electrical heater of positioning motor 8.1, which is in the form of a shape-memory element, is de-energized, the wax contracts, and the plunger of positioning motor 8.1 is moved substantially along the longitudinal axis of rod 8.2 in the opposite direction, i.e., away from door 6. The automatic return of door 6 from the open position to the closed position takes place analogously to the above-described movement from the closed position to the open position, but in the opposite direction. Unlike the previous case, the movement of door 6 from the open position back to the closed position is assisted by the return element.

[0026] The invention is not limited to the exemplary embodiment described above. For example, it is possible to use a positioning motor in the form of an electric motor or a solenoid, or to use other shape-memory materials. In addition to using temperature as the physical quantity, as in the illustrated exemplary embodiment, it is also possible to use other physical quantities, such as relative humidity or time, depending on whether the physical quantity is measured in or on the cooking chamber by sensor means, or whether the reaching of the threshold value is calculated based on data stored in the memory of the cooking appliance control system. This data may be determined in advance in a series of experiments. Moreover, it is conceivable that the threshold value of the physical quantity used may be predetermined, for example, depending on the food to be cooked and/or on the type of

cooking process. Furthermore, it is possible to use a damping means instead of the spring means.

~~What is claimed is:~~

1. A method for operating a cooking appliance including a cooking chamber, which is bounded by a housing and a door in its closed position, and further including a cooking appliance control system, the door being automatically openable by the cooking appliance control system by means of a door opening device, the door being automatically moved from the closed position to the open position when the cooking process is complete, wherein, after the aforementioned movement to the open position, the door (6) is automatically returned to the closed position when a physical quantity falls below a predetermined threshold value stored in a memory of the cooking appliance control system.

2. — A cooking appliance, in particular a steam cooking appliance, for carrying out the method according to Claim 1, comprising a cooking chamber which is bounded by a housing and a door in its closed position, and further comprising a cooking appliance control system, the door being automatically openable by the cooking appliance control system by means of a door opening device, the door opening device including a positioning motor and a rod, and the rod being capable of being automatically reciprocated by the cooking appliance control system by means of the positioning motor such a manner that the door can be automatically moved from its closed position to a predetermined open position and vice versa, the cooking appliance control system actuating the positioning motor as a function of the output signal of a sensor located in the cooking chamber, and the cooking appliance control system actuating the positioning motor in such a manner that the door is automatically moved from the closed position to the open position when the cooking process is complete, wherein the rod (8.2) can be reciprocated in a guide means (8.3), and the cooking appliance control system actuates the positioning motor (8.1) in such a manner that the door (6) is automatically returned to the closed position when a physical quantity falls below a predetermined threshold value stored in the memory.

~~3. The cooking appliance as recited in Claim 2,
wherein the positioning motor (8.1) takes the form of an electrically heatable shape-memory
element.~~

~~4. The cooking appliance as recited in one of the Claims 2 or 3,~~

~~wherein the returning of the door (6) from the open position to the closed position is aided by a return element which is disposed between the door (6) and the housing (4) and is in force-transmitting connection with the door (6) and the housing (4).~~

~~5. — The cooking appliance as recited in one of Claims 2 to 4, wherein a spring means (8.4) or a damping means is mounted on the rod (8.2) in such a manner that the movement of the door (6) from the closed position to the open position, or vice versa, is retarded.~~

Abstract

The present invention relates to a method for operating a cooking appliance including a cooking chamber, which is bounded by a housing and a door in its closed position, and further including a cooking appliance control system, the door being automatically openable by the cooking appliance control system by means of a door opening device.

In order to further improve the ease of use for the user, the door (6) is automatically moved from the closed position to the open position when the cooking process is complete, and subsequently automatically returned to the closed position when a physical quantity falls below a predetermined threshold value stored in a memory of the cooking appliance control system.

The present invention also relates to a device for carrying out the method according to the present invention.